



Significant reduction in collection costs



Online monitoring via portal or app, anywhere and anytime



Reduction of CO2 emissions through efficient waste collection



Vandal-proof due to robust material



Insert without touching by means of a foot pedal



For standard 240 liter wheelie bin





Procomat B.V.

De Donge 2b

5684 PX Best

The Netherlands

T: (+31) 499 747004

E: info@procomat.nl

W: procomat.nl

#### Material

Footpedal

Door and body Hopper assembly Base Powdercoated steel 2 mm Stainless steel 316 2 mm Stainless steel 304 3 mm Galvanized steel 8 mm

#### **Dimensions**

Height

Width incl. hinge

Depth

Throw-in height

Throw-in width

Drop-in opening "open hatch"

Drop-in opening "closed hatch"

Weight without wheelie bin

Content wheelie bin

1.630 mm

690 mm

810 mm

1.300 mm


385 mm

385 x 140 mm

385 x 125 mm

185 kg

240 litre



## **Technical specifications**

Compactor type

Battery type

Number of batteries

System power

Compression ratio (waste)

Compression ratio (fast food)

Data connection

Data portal

Solar panel capacity

Electric linear press 12V, 41Ah gel

- 1

115W

> 5x (1.200 litre)

> 8x (1.920 litre

2G / 3G / 4G

cleancitymanager.con

30W

### Standard

- ✓ Footpedal
- ✓ Solar panel
- ✓ LED filling level indicator
- ✓ Fill level sensor
- ✓ Keyless (RFID) door control
- ✓ Blue LED night illumination
- ✓ GPS positionering
- ✓ Remote (un)lock control
- ✓ Non-stop throw in
- ✓ Compact loader, compatible
- ✓ CleanCityManager, first year free
- ✓ Soft close hopper system
- ✓ Installation and lifting set

# Optional

- 1.8 litre ashtray set (stainless steel)
- Sound system
- Second LED filling level on back
- O Wheelie bin 240 litre HDPE, EN840-1
- O RAL colour of choice > 10 pieces
- RFID Collector and Lock pass
- Waste bags, extra strong
- Application Programming Interface (API)
- CleanCityManager, extension
- Wrapping, signage
- O Concrete foundation 600 x 600 x 200 mm, 172,8 kg
- O Galvanized foundation plate 985 x 960 x 12 mm, 90 kg
- Anti-grafitti coating
- O Parts in stainless steel 304 of 316
- Service and installation agreement
- Closed hatch in combination with foot pedal



