



INTERIOR-WAX

Hard-wearing finish with a wax-like character for wood for interior use!



7393 White
Transparent



7394 White
Opaque



PRODUCT DESCRIPTION

Transparent or opaque, satin and hard-wearing wood finish with a wax-like character for indoor areas.

Osmo Interior-Wax is stain-resistant, water-repellent and abrasion-resistant and results in a surface that is pleasant to the touch. The wood grain remains visible. Simple application – without primer or intermediate sanding – this saves time and money.

Suitable for wood; microporous surface will not crack, peel or flake.

The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

RECOMMENDED USE

Osmo Interior-Wax is suitable for the protection and decorative finishing of wood in indoor areas: wall and ceiling panelling, moulding and beams as well as furniture, doors and children's toys. It is also suitable for recoating and repairing wood factory finished with Osmo Interior-Wax White Transparent (7393) or White Opaque (7394) and for recoating old wooden ceiling panelling.

INGREDIENTS

Based on a polymer dispersion and waxes, titanium dioxide (white pigment), additives and preservatives. Solvent: water. EU limit value for this product (cat. A/d): 130 g/l VOC (2010).

This product contains max. 90 g/l VOC. Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 1,10-1,25 g/cm³

Viscosity: 1300-1700 mPas viscid

pH value: 8.0-9.0

Odour: faint/mild, odourless after drying

Flash point: not applicable

STORAGE

Up to 2 years and longer if can is kept dry, closed tightly and stored at temperatures between 5° and 35°C. Do not expose to frost during transport and storage.

SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 18%, apply at min. +10° C).

Osmo Interior-Wax is ready to use. Do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works. Fill small cracks, larger joints or holes in wood (with Osmo Wood Filler). Wood treated with Osmo Interior-Wax generally only needs cleaning and recoating.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

METHODS OF APPLICATION

With Osmo Flat Brush or Microfibre Roller, apply thinly and quickly length by length along the wood grain and spread well.

Allow to dry for 3-4 hours under good ventilation.

If necessary, sand surface with fine sandpaper (grit P360) before applying the second coat.

After drying, quickly apply a second coat also thinly.

For renovation works, one coat applied to the clean and dry surface is usually sufficient.

CLEANING OF TOOLS

Immediately after use, with soap and water.

DRYING TIME

Approx. 3-4 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.



COVERAGE

1 litre covers approx. 16 m² with one coat.
Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

NOTE

One coat of Interior-Wax White Opaque creates a more intensive colour than two coats of Interior-Wax White Transparent.

CAUTION

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. Avoid breathing mist/vapours/spray. If in eyes: Rinse cautiously with water for several minutes.
Safety data sheet available on request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 12). Only completely emptied cans can be recycled.

COLOUR TONES

7393 White Transparent
7394 White Opaque

CAN SIZES

0.75 L, 2.50 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 02/17